# DNP

# **DSCR**

**Universal Care** Resin

**Technical Data Sheet** 



# **Product Description**

DSCR is an durable resin for special garment care applications. With incredible steam resistant qualities, this ribbon is dry clean and laundry safe. This highly versatile ribbon prints on woven and nonwoven fabrics, films, synthetics and satins. DSCR utilizes less energy, and provides superior scratch, heat, and water resistance.

# **Applications**







Retail



**Pharmaceutical** 



Food & Beverage



**Beauty** 

### **Recommended Substrates**

**Specialty Materials** 













#### **Performance Characteristics**

- ✓ Halogen-free
- Excellent resistance to washing and dry cleaning
- Superior print quality at low energy levels
- Extreme resistance to scratching and smudging
- Available for both flat head and near edge printers
- OEKO-TEX Standard 100 Class 1 KL003 191447.1



| RIBBON PROPERTIES   |            |             |  |
|---------------------|------------|-------------|--|
| Description         | Result     | Test Method |  |
| Ink                 | Resin      |             |  |
| Color               | Black      | Visual      |  |
| Total Thickness     | 7.4 ± 0.5µ | Weight      |  |
| Base Film Thickness | 4.5 ± 0.5µ | Weight      |  |

| DURABILITY OF PRINTED IMAGE |            |                                                                                     |
|-----------------------------|------------|-------------------------------------------------------------------------------------|
| Description                 | Result     | Test Method                                                                         |
| Print Density               | > 2.07     | Densitometer                                                                        |
| Smudge Resistance           | <b>A</b> * | Colorfastness Tester - 400 Cycles<br>@ 500 Grams with Cotton Cloth                  |
| Scratch Resistance          | A*         | Colorfastness Tester - 50 Cycles<br>@ 200 Grams with Stainless Steel<br>Pointed Tip |

Label Stock: Top-coated Polyester

Print Speed: 4 IPS

\*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.







The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

#### DNP IMAGINGCOMM ASIA SDN. BHD.







