DNP

DSR

DS Series Resin



Technical Data Sheet

Product Description

DSR is a reliable, cost-effective solution for a wide range of resin applications. DSR outperforms the competition in abrasion and solvent resistance, uses less print energy and is designed with DNP's standard anti-static and backcoat properties to protect and extend the life of printheads.

Applications



Automotive



Chemicals



Electronics



Food & Beverage



Health & **Beauty**



Inventory & Logistics



Outdoor



Pharmaceutical

Recommended Substrates

Synthetics

Polyester Polypropylene Polyethylene Polyolefin Vinyl









Performance Characteristics

- Good sensitivity (high definition characters)
- Halogen-free
- Extreme durability and solvent resistance
- Extensive label adaptability expanding application options
- Unmatched scratch and heat resistance
- Unbeatable edge definition for dark, dense images and improved scan rates
- DNP's specially formulated backcoating for printhead protection
- Anti-static for easy handling and extended printhead life





RIBBON PROPERTIES			
Description	Result	Test Method	
Ink	Resin		
Color	Black	Visual	
Total Thickness	5.8 ± 0.9µ	Weight	
Base Film Thickness	4.5 ± 0.4µ	Weight	

DURABILITY OF PRINTED IMAGE			
Description	Result	Test Method	
Print Density	> 1.80	Densitometer	
Smudge Resistance	A*	Colorfastness Tester - 100 Cycles @ 500 Grams with Cotton Cloth	
Scratch Resistance	A *	Colorfastness Tester - 50 Cycles @ 200 Grams with Stainless Steel Pointed Tip	

Label Stock: Top-coated Polyester

Print Speed: 6 IPS

*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.







The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP IMAGINGCOMM ASIA SDN. BHD.









