DNP

TR4070

Classic Resin



Technical Data Sheet

Product Description

DNP's TR4070 carries widespread agency approval, including meeting the FDA's requirements for indirect food contact. In addition to superior performance for compliance applications, this ribbon eliminates the need for overlaminates. TR4070 features our specially formulated backcoat technology as well as DNP's exclusive anti-static properties for easy handling and unrivalled printhead protection.

Applications







Chemicals



Electronics



Health & Beauty



Inventory & Logistics



Outdoor



Pharmaceutical

Recommended Substrates

Synthetics

Polyester

Specialty Materials





Performance Characteristics

- ✓ Halogen-free
- Eliminates the need for overlaminates in many cases
- Excellent smudge and scratch resistance
- Anti-static for easy handling and extended printhead life
- ✓ DNP's specially formulated backcoating for printhead protection
- Unbeatable edge definition ensuring dark, dense images and improved scan rates





RIBBON PROPERTIES			
Description	Result	Test Method	
Ink	Resin		
Color	Black	Visual	
Total Thickness	6.3 ± 0.9µ	Weight	
Base Film Thickness	4.5 ± 0.4µ	Weight	

DURABILITY OF PRINTED IMAGE			
Description	Result	Test Method	
Print Density	> 1.60	Densitometer	
Smudge Resistance	A*	Colorfastness Tester - 100 Cycles @ 500 Grams with Cotton Cloth	
Scratch Resistance	A *	Colorfastness Tester - 50 Cycles @ 200 Grams with Stainless Steel Pointed Tip	

Label Stock: Top-coated Polyester

Print Speed: 6 IPS

*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.







The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP IMAGINGCOMM ASIA SDN. BHD.





